



SAFETY DATA SHEET

1. Identification

Product identifier	LPS® HDX (Aerosol)
Other means of identification	
Part Number	01020
Recommended use	A degreaser designed to remove grease, oil, dirt and other residues from metal and other hard surfaces near ignition sources.
Recommended restrictions	None known.
Manufacturer/Importer/Supplier/Distributor information	
Manufacturer	
Manufacturer	
Company name	ITW Pro Brands
Address	4647 Hugh Howell Rd. Tucker, GA 30084
Country	(U.S.A.) Tel: +1 770-243-8800
In Case of Emergency	1-800-424-9300 (inside U.S.) +001 703-527-3887 (outside U.S.)
Website	www.lpslabs.com
E-mail	lpssds@itwprobrands.com

2. Hazard(s) identification

Physical hazards	Gases under pressure	Compressed gas
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Germ cell mutagenicity	Category 2
	Carcinogenicity	Category 1B
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
Environmental hazards	Not classified.	
OSHA defined hazards	Not classified.	
Label elements		



Signal word	Danger
Hazard statement	Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye irritation. Suspected of causing genetic defects. May cause cancer. May cause drowsiness or dizziness.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight.

Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
1,1,2-trichloroethylene		79-01-6	90 - 100
Carbon Dioxide		124-38-9	1 - 5

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Ingestion	Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.
Most important symptoms/effects, acute and delayed	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Cool containers exposed to flames with water until well after the fire is out.
General fire hazards	Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.
--	--

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Store locked up. Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Butanone (CAS 78-93-3)	PEL	590 mg/m3 200 ppm	
Camphor USP (CAS 76-22-2)	PEL	2 mg/m3	
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3	
Diphenyl Oxide (CAS 101-84-8)	PEL	5000 ppm 7 mg/m3	Vapor.
Iso amyl acetate (CAS 123-92-2)	PEL	1 ppm 525 mg/m3	Vapor.
Turpentine (CAS 8006-64-2)	PEL	100 ppm 560 mg/m3	
		100 ppm	

US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
1,1,2-trichloroethylene (CAS 79-01-6)	Ceiling	200 ppm
	TWA	100 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
1,1,2-trichloroethylene (CAS 79-01-6)	STEL	25 ppm	
	TWA	10 ppm	
Butanone (CAS 78-93-3)	STEL	300 ppm	
	TWA	200 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Camphor USP (CAS 76-22-2)	STEL	3 ppm	
	TWA	2 ppm	
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm	
	TWA	5000 ppm	
Diphenyl Oxide (CAS 101-84-8)	STEL	2 ppm	Vapor.
	TWA	1 ppm	Vapor.
Iso amyl acetate (CAS 123-92-2)	STEL	100 ppm	
	TWA	50 ppm	
Turpentine (CAS 8006-64-2)	TWA	20 ppm	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
1,1,2-trichloroethylene (CAS 79-01-6)	TWA	25 ppm	
Butanone (CAS 78-93-3)	STEL	885 mg/m3	
		300 ppm	
	TWA	590 mg/m3	
Camphor USP (CAS 76-22-2)	TWA	200 ppm	
		2 mg/m3	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
		30000 ppm	
	TWA	9000 mg/m3	
Diphenyl Oxide (CAS 101-84-8)	TWA	5000 ppm	
		7 mg/m3	Vapor.
Iso amyl acetate (CAS 123-92-2)	TWA	1 ppm	Vapor.
		525 mg/m3	
Turpentine (CAS 8006-64-2)	TWA	100 ppm	
		560 mg/m3	
		100 ppm	

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
1,2 Butylene Oxide (CAS 106-88-7)	TWA	5.9 mg/m3
		2 ppm

Biological limit values**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
1,1,2-trichloroethylene (CAS 79-01-6)	15 mg/l	Trichloroacetic acid	Urine	*
	0.5 mg/l	Trichloroethano l, without hydrolysis	Blood	*
Butanone (CAS 78-93-3)	2 mg/l	MEK	Urine	*

* - For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves.
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Gas.
Form	Aerosol.
Color	Clear. Colorless.

Odor Sweet. Spice.

Odor threshold Not established

pH Not applicable

Melting point/freezing point Not established

Initial boiling point and boiling range 188.6 °F (87 °C)

Flash point Tag Closed Cup (None)

Evaporation rate 0.3 (Ethyl Ether = 1)

Flammability (solid, gas) Non flammable gas.

Upper/lower flammability or explosive limits

Flammability limit - lower (%) 8 %

Flammability limit - upper (%) 10.5 %

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 58 mm Hg @ 20°C

Vapor density 4.5

Relative density Not available.

Solubility(ies)

Solubility (water) 0.1 %

Partition coefficient (n-octanol/water) 2.4

Auto-ignition temperature > 788 °F (> 420 °C)

Decomposition temperature Not established

Viscosity 0.53 cP @ 25° C

Other information

Explosive properties Not explosive.

Heat of combustion < 20 kJ/g

Oxidizing properties Not oxidizing.

Percent volatile 100 %

Specific gravity 1.41 - 1.47 @ 20°C

VOC 97.8 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Heat. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity Narcotic effects.

Components	Species	Test Results
1,1,2-trichloroethylene (CAS 79-01-6)		
Acute		
Dermal		
LD50	Rabbit	20 ml/kg
Inhalation		
LC50	Rat	12500 ppm, 4 Hours
Oral		
LD50	Rat	4920 mg/kg
1,2 Butylene Oxide (CAS 106-88-7)		
Acute		
Dermal		
LD50	Rabbit	1.77 ml/kg, 24 Hours
Inhalation		
<i>Vapor</i>		
LC50	Rat	> 6.3 mg/l, 4 Hours
Oral		
LD50	Rat	1100 µl/kg
Butanone (CAS 78-93-3)		
Acute		
Dermal		
LD50	Rabbit	> 10 ml/kg
Oral		
LD50	Rat	2054 mg/kg
Diphenyl Oxide (CAS 101-84-8)		
Acute		
Oral		
LD50	Rat	2.83 g/kg

Components	Species	Test Results
Turpentine (CAS 8006-64-2)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation		
<i>Vapor</i>		
LC50	Rat	13.7 mg/l, 4 Hours
Oral		
LD50	Rat	4.6 ml/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory or skin sensitization		
ACGIH sensitization		
Turpentine (CAS 8006-64-2)	Dermal sensitization	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Germ cell mutagenicity	Suspected of causing genetic defects.	
Carcinogenicity	May cause cancer.	
ACGIH Carcinogens		
1,1,2-trichloroethylene (CAS 79-01-6)	A2 Suspected human carcinogen.	
Camphor USP (CAS 76-22-2)	A4 Not classifiable as a human carcinogen.	
Turpentine (CAS 8006-64-2)	A4 Not classifiable as a human carcinogen.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
1,1,2-trichloroethylene (CAS 79-01-6)	1 Carcinogenic to humans.	
1,2 Butylene Oxide (CAS 106-88-7)	2B Possibly carcinogenic to humans.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
Not regulated.		
US. National Toxicology Program (NTP) Report on Carcinogens		
1,1,2-trichloroethylene (CAS 79-01-6)	Reasonably Anticipated to be a Human Carcinogen.	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	May cause drowsiness and dizziness.	
Specific target organ toxicity - repeated exposure	Not classified.	
Aspiration hazard	Not an aspiration hazard.	
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.	
Further information	Symptoms may be delayed.	

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
1,1,2-trichloroethylene (CAS 79-01-6)		
Aquatic		
Fish	LC50	Flagfish (<i>Jordanella floridae</i>)
3.1 mg/l, 96 hours		
Butanone (CAS 78-93-3)		
Aquatic		
Crustacea	EC50	Water flea (<i>Daphnia magna</i>)
4025 - 6440 mg/l, 48 hours		
Fish	LC50	Sheepshead minnow (<i>Cyprinodon variegatus</i>)
> 400 mg/l, 96 hours		

Components	Species	Test Results
Diphenyl Oxide (CAS 101-84-8)		
Aquatic		
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus) 1.8 - 3.2 mg/l, 96 hours
Persistence and degradability	Not inherently biodegradable.	
Bioaccumulative potential		
Partition coefficient n-octanol / water (log Kow)		
LPS® HDX (Aerosol)		2.4
1,1,2-trichloroethylene		2.61
Butanone		0.29
Diphenyl Oxide		4.21
Mobility in soil	No data available.	
Other adverse effects	None known.	
13. Disposal considerations		
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with all applicable regulations.	
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.	
	D003: Waste Reactive material D040: Waste Trichloroethylene	
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).	
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.	
14. Transport information		
DOT		
UN number	UN1950	
UN proper shipping name	Aerosols, non-flammable, (each not exceeding 1 L capacity)	
Transport hazard class(es)		
Class	2.2	
Subsidiary risk	6.1(PGIII)	
Label(s)	2.2	
Packing group	Not applicable.	
Environmental hazards		
Marine pollutant	No	
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.	
Packaging exceptions	306	
Packaging non bulk	None	
Packaging bulk	None	
IATA		
UN number	UN1950	
UN proper shipping name	Aerosols, non-flammable	
Transport hazard class(es)		
Class	2.2	
Subsidiary risk	6.1(PGIII)	
Packing group	Not applicable.	
Environmental hazards	No	
ERG Code	2L	
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.	
Other information		
Passenger and cargo aircraft	Allowed with restrictions.	

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1950
UN proper shipping name AEROSOLS
Transport hazard class(es)
Class 2.2
Subsidiary risk 6.1(PGIII)
Packing group Not applicable.
Environmental hazards
Marine pollutant No
EmS F-D, S-U
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

DOT



IATA; IMDG



General information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

1,1,2-trichloroethylene (CAS 79-01-6) 0.1 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

1,1,2-trichloroethylene (CAS 79-01-6) Listed.
1,2 Butylene Oxide (CAS 106-88-7) Listed.
Butanone (CAS 78-93-3) Listed.
Iso amyl acetate (CAS 123-92-2) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
 Delayed Hazard - Yes
 Fire Hazard - No
 Pressure Hazard - Yes
 Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
TRICHLOROETHYLENE	79-01-6	97.25

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

1,1,2-trichloroethylene (CAS 79-01-6)
 1,2 Butylene Oxide (CAS 106-88-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Butanone (CAS 78-93-3) 6714

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Butanone (CAS 78-93-3) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Butanone (CAS 78-93-3) 6714

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Butanone (CAS 78-93-3) Low priority
 Diphenyl Oxide (CAS 101-84-8) Low priority
 Iso amyl acetate (CAS 123-92-2) Low priority

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,1,2-trichloroethylene (CAS 79-01-6) Listed: April 1, 1988

US - California Proposition 65 - CRT: Listed date/Developmental toxin

1,1,2-trichloroethylene (CAS 79-01-6) Listed: Jan 31, 2014

US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

1,1,2-trichloroethylene (CAS 79-01-6) Listed: Jan 31, 2014

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,1,2-trichloroethylene (CAS 79-01-6)
 1,2 Butylene Oxide (CAS 106-88-7)
 Butanone (CAS 78-93-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 10-18-2016

Version # 01

Disclaimer ITW Pro Brands cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information This document has undergone significant changes and should be reviewed in its entirety.