


SERIES 41 MANIFOLDS

°F and °C with 2-1/2" (63.5 mm) gauges



Forged body is solid brass for durability. Full porting maximizes capacity. Metal valve handles are full size for easy operation. Hose anchors are forged into back of body at 45°.

- Flutterless™ technology means surge protector and silicone dampened movement helps minimize needle pulsation for easier, more accurate readings
- Sliding double "O" ring pistons reduces wear
- Most manifolds include color-coded YELLOW JACKET® charging hoses
- Easy-to-read 2-1/2" (63.5 mm) steel case gauges with 3-2-3% accuracy (Class B)
- Limited lifetime warranty on manifold bar and valves – not gauges. See warranty information for details
- Made in the USA 



Series 41 Manifolds

UPC#	Description - °F and °C - Red/Blue	Scale	Refrigerant
42051	Heat pump manifold only, 1/4-5/16-1/4"	bar/psi	R-410A
42054	With 60" black PLUS II™ hoses (two 1/4x5/16" ball valve and one 1/4x1/4" ball valve)	bar/psi	
42045	A2L Heat pump manifold only	psi	R-32/454B/410A
42046	A2L Heat pump manifold With 60" black PLUS II™ 1/4" hoses	psi	
49123	High side replacement A2L heat pump gauge	psi	R-410A
49124	Low side replacement A2L heat pump gauge	psi	
41712	Manifold only	kg/cm ² /psi	
41703	With 60" PLUS II™ FLEXFLOW™ hoses	kg/cm ² /psi	
41709	With 60" PLUS II™ standard fittings	kg/cm ² /psi	
41715*	With 60" PLUS II™ standard fittings	kg/cm ² /psi	
41710	With 60" PLUS II™ heavy duty black standard fittings	kg/cm ² /psi	
41702	With 60" PLUS II™ heavy duty black compact ball valve fittings	kg/cm ² /psi	
42715	With 60" PLUS II™ compact ball valve fittings	kg/cm ² /psi	
41711*	With 60" PLUS II™ compact ball valve fittings	kg/cm ² /psi	
41652	Manifold only with 5/16, 1/4", 5/16" hose fittings	bar/psi	R-32/410A
UPC#	Description - °F - Red/Blue	Scale	Refrigerant
41212	Manifold only	psi	R-12/22/502
41213	With 36" PLUS II™ standard fittings	psi	
41220	With 48" PLUS II™ standard fittings	psi	
41215	With 60" PLUS II™ standard fittings	psi	
41219	With 72" PLUS II™ standard fittings	psi	
44213	With 36" PLUS II™ SealRight fittings	psi	
44220	With 48" PLUS II™ SealRight fittings	psi	
44215	With 60" PLUS II™ SealRight fittings	psi	
44219	With 72" PLUS II™ SealRight fittings	psi	
42215	With 60" PLUS II™ compact ball valve fittings	psi	
42219	With 72" PLUS II™ compact ball valve fittings	psi	
41312	Manifold only	psi	R-134a/404A/507
41313	With 36" PLUS II™ standard fittings	psi	
41311	With 48" PLUS II™ standard fittings	psi	
41315	With 60" PLUS II™ standard fittings	psi	
41319	With 72" PLUS II™ standard fittings	psi	
43313	With 36" PLUS II™ standard fittings	psi	
44313	With 36" PLUS II™ SealRight fittings	psi	
44315	With 60" PLUS II™ SealRight fittings	psi	
44319	With 72" PLUS II™ SealRight fittings	psi	
42315	With 60" PLUS II™ compact ball valve fittings	psi	
41202	Manifold only	psi	R-22/134a/404A
41209	With 36" PLUS II™ standard fittings	psi	
41211	With 60" PLUS II™ standard fittings	psi	
UPC#	Description - °C - Red/Blue	Scale	Refrigerant
41292	Manifold only	kg/cm ² /psi	R-12/22/502
41293	With 36" PLUS II™ standard fittings	kg/cm ² /psi	
41295	With 60" PLUS II™ standard fittings	kg/cm ² /psi	
41299	With 72" PLUS II™ standard fittings	kg/cm ² /psi	
41382	Manifold only	bar/psi	R-134a/404A/507
41353	Manifold with 36" PLUS II™ standard fittings	bar/psi	
41355	Manifold with 60" PLUS II™ standard fittings	bar/psi	
43355	Manifold with 60" PLUS II™ standard fittings	bar/psi	
41392	Manifold only	kg/cm ² /psi	
41363	Manifold with 36" PLUS II™ standard fittings	kg/cm ² /psi	
41365	Manifold with 60" PLUS II™ standard fittings	kg/cm ² /psi	
43365	Manifold with 60" PLUS II™ standard fittings	kg/cm ² /psi	
41332	Manifold only	bar/psi	R-134a/404A/407C
40944	Manifold only with 1/4" ports and 5/16" hose fittings	bar/MPa	R-410A
41781	Manifold only with 5/16" fittings	bar/MPa	
41780	Manifold only with 1/4" fittings	bar/MPa	

*Special R-410A hose - R/B hoses are 1/4" x 45° 5/16" end; Y hose is 1/4" x 45° 1/4" end.

For replacement parts, refer to the manual (also available at yellowjacket.com)